



Cham Paper Group

Technical Data Sheet

Name ADICAR S3

Structure



Features

- One side double coated label paper with reverse side coat
- High gloss level and brightness
- Very good results in flexo, letterpress and offset printing
- Application: face stock for self adhesive labels

Specifications

Target values at 23°C / 50% R.H. for general guidance only	Methods	Units	
Substance	ISO 536	g/m ²	83.0
Thickness	ISO 534	µm	65.0
Brightness R457	DIN 53145	%	95.0
Opacity	ISO 2471	%	85.0
Gloss level 75° coated side	ISO 8254-1	%	90.0
Roughness PPS H10 coated side	ISO 8791-4	µm*100	100.0
Roughness PPS H10 reverse side	ISO 8791-4	µm*100	230.0
Tensile strength MD	ISO 1924	N/15mm	72.0
Tensile strength CD	ISO 1924	N/15mm	40.0

Edition: November 13

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cham guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.