



Cham Paper Group

Technical Data Sheet

Name **CARCOAT OB EXTRA**

Structure



Features

- One side double layer clay coated Kraft paper
- High calendered (super calander)
- Extraordinary high gloss and smoothness
- Excellent flexo and rotogravure printability
- Excellent flex crack resistance
- Neutral test and odour
- Excellent runnability on the converting and packaging side
- Application: Universal use for flexible packaging applications
- Conformity: BfR (German Federal Institute for Risk Estimation), FDA, Italian Law

Specifications

Target values at 23°C / 50% r.H. for general guidance only	Methods	Units				
Substance	ISO 536	g/m ²	74.0	80.0	83.0	90.0
Brightness R457	DIN	%	88.0	88.0	88.0	88.0
Opacity	ISO 2471	%	83.0	85.0	86.0	87.0
Gloss Lehmann 75°	ISO 8254-	%	80.0	80.0	80.0	80.0
Roughness PPS H10 coated side	ISO 8791-	µm*100	90.0	90.0	90.0	100.0
Tensile strength MD	ISO 1924	N/15mm	63.0	65.0	68.0	73.0
Tensile strength CD	ISO 1924	N/15mm	36.0	38.0	40.0	42.0
Elongation M.D.	ISO 1924	%	2.0	2.0	2.0	2.0
Elongation C.D.	ISO 1924	%	6.0	6.0	6.0	6.0
Bursting strength	ISO 2758	kPa	190.0	195.0	200.0	210.0

Edition: April 2013

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cartiera di Carmignano guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.