



Cham Paper Group

Technical Data Sheet

Name **CARCOAT SATIN OB**

Structure



Features

- One side double layer clay coated Kraft paper
- High brightness
- Extra matt surface
- Excellent runnability
- Good results in rotogravure and flexo printing
- Application: Universal use for most flexible packaging applications
- Conformity: BfR (German Federal Institute for Risk Estimation), FDA, Italian Law

Specifications (provisional)

Target values at 23°C / 50% r.H. for general guidance only	Methods	Units	provisional	provisional
Substance	ISO 536	g/m ²	70.0	80.0
Brightness R457	DIN 53145	%	95.0	95.0
Opacity	ISO 2471	%	86.0	88.0
Gloss Lehmann 75° coated side	ISO 8254-1	%	22.0	22.0
Roughness PPS H10 coated side	ISO 8791-4	µm*100	165.0	165.0
Tensile strength MD	ISO 1924	N/15mm	62.0	72.0
Tensile strength CD	ISO 1924	N/15mm	33.0	38.0

Edition: March 14

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cartiera di Carmignano guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.