



Cham Paper Group

Technical Data Sheet

Name FLEXCAR 1

Structure

Kraft paper

Features

- New generation of an anti-mould paper
- Uncoated calendered kraft paper
- Anti-mould treatment (Intace B-9713)
- Excellent light fastness
- Good opacity
- Excellent surface for top results in flexo printing and lamination
- Suitable for hot-melt treatment
- Application: Soap wrap bars

Specifications

Target values at 23°C / 50% r.H. for general guidance only	Methods	Units			*
Substance	ISO 536	g/m ²	50.0	60.0	70.0
Brightness R457	DIN 53145	%	84.0	84.0	84.0
Opacity	ISO 2471	%	75.0	78.0	81.0
Roughness PPS (S10) W.S.	ISO 8791-4	µm*100	310.0	310.0	310.0
Roughness PPS (S10) F.S.	ISO 8791-4	µm*100	240.0	240.0	240.0
Tensile strength MD	ISO 1924	N/15mm	47.0	55.0	63.0
Tensile strength CD	ISO 1924	N/15mm	27.0	32.0	37.0
Bursting strength	ISO 2758	kPa	130.0	150.0	175.0
Anti-mould treatment (B-9713)	Internal method	ppm	Min.1000	Min.1000	Min.1000

* Provisional

Edition: February 2014

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cartiera di Carmignano guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.

CHAM PAPER GROUP ITALIA S.P.A. Via Roma 67 I-35010 Carmignano di Brenta (PD), Italy Phone +39 049 94 23 600
Fax +39 049 94 23 700 mail.carmignano@cham-group.com www.cham-group.com