



Cham Paper Group

Technical Data Sheet

Name INNERLINER PRISMA 2

Structure



Features

- One side double layer clay coated Kraft paper, supercalendered
- Smooth surface for good rotogravure and flexo printing results
- Suitable for water and solvent based lacquer system
- No OBA added
- High calendered (super calender)
- Excellent metallization properties
- Odorless and taint-free
- Application: Metallized Innerliner for cigarette soft packs
- Conformity: BfR (German Federal Institute for Risk Estimation)

Specifications

Target values at 23°C / 50% r.H. for general guidance only	Methods	Units	
Substance	ISO 536	g/m ²	83.0
Thickness	ISO 534	µm	74.0
Gloss Lehmann 75° coated side	ISO 8254-1	%	78.0
Tensile strength MD	ISO 1924	N/15m	72.0
Tensile strength CD	ISO 1924	N/15m	46.0
Roughness PPS H10 coated side	ISO 8791-4	µmx10	100
Absolute humidity	ISO 287	%	4.0

Edition: April 2014

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cartiera di Carmignano guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.