



# Cham Paper Group

## Technical Data Sheet

**Name** **KRAFT PSL**

### Structure



### Features

- One side double coated Kraft paper, calendered
- Smooth surface and even surface suitable for primer, lacquer and coating treatments
- Excellent runnability properties
- Good heating stability
- Used as protective for multi-layer coating
- Conformity: BfR (German Federal Institute for Risk Estimation), FDA, Italian Law

### Specifications (Provisional)

Target values at 23°C / 50% r.H. for general guidance only	Methods	Units	
Substance	ISO 536	g/m <sup>2</sup>	105.0
Thickness	DIN 53145	um	95.0
Tearing resistance MD	DIN 21974	mN	650.0
Tearing resistance CD	DIN 21974	mN	750.0
Gloss Lehmann 75°	ISO 8254-1	%	70.0
Roughness PPS H10 coated	ISO 8791-4	um*100	110.0

Edition: December 13

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cartiera di Carmignano guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.

**CHAM PAPER GROUP ITALIA S.P.A.** Via Roma 67 I-35010 Carmignano di Brenta (PD), Italy Phone +39 049 94 23 600  
Fax +39 049 94 23 700 mail.carmignano@cham-group.com [www.cham-group.com](http://www.cham-group.com)