



Cham Paper Group

Technical Data Sheet

Name LABELCAR G1

Structure



Features

- One side coated Kraft paper
- Low wet strength and alkali-resistant
- Good results in flexo, rotogravure and offset printing
- Application: labels for non-returnable bottles

Specifications

Target values at 23°C / 50% R.H. for general guidance only	Methods	Units				
Substance	ISO 536	g/m ²	68.0	70.0	73.0	75.0
Thickness	ISO 534	µm	63.0	65.0	69.0	70.0
Brightness R457	DIN 53145	%	94.0	94.0	94.0	94.0
Gloss Lehmann 75° WS	ISO 8254-1	%	62.0	62.0	62.0	62.0
Roughness PPS H10 WS	ISO 8791-4	µm*100	120.0	120.0	120.0	120.0
Tensile strength MD	ISO 1924	N/15mm	55.0	58.0	62.0	64.0
Tensile strength CD	ISO 1924	N/15mm	36.0	39.0	42.0	43.0
Wet tensile strength 5 min.	ISO 3781	N/15mm	13.0	13.0	13.5	14.0
Absolute humidity	ISO 287	%	5.5	5.5	5.5	5.5

Edition: November 13

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cham guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.