



# Cham Paper Group

## Technical Data Sheet

**Name** **Silco Larice 2**

**Structure**



**Features**

- Glassine paper
- Highly calendered
- Good transparency
- Good smoothness
- Suitable for solvent and solventless silicone
- Colour: Larice (Larch)
- Application: Siliconized base paper for self adhesive labels (in rolls)

**Specifications**

Target values at 23°C / 50% r. H. for general guidance only	Methods	Units				
Substance	ISO 536	g/m <sup>2</sup>	58.0	60.0	62.0	80.0
Thickness	ISO 534	µm	51.0	53.0	54.0	68.0
Roughness PPS siliconizing side	ISO 8791-4	µm*100	180.0	180.0	180.0	180.0
Tensile strength MD	ISO 1924	N/15mm	84.0	88.0	92.0	121.0
Tensile strength CD	ISO 1924	N/15mm	48.0	53.0	54.0	70.0
Transparency	DIN 53147	%	53.0	53.0	52.0	-
Cobb Unger 120 sec. siliconizing side	Internal method	g/m <sup>2</sup>	0.8	0.8	0.8	0.8

Edition: July 13

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cartiera di Carmignano guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.