



Cham Paper Group

Technical Data Sheet

Name **Silco White BS**

Structure



Features

- Glassine paper for silicone treatment on both sides
- Good smoothness on both sides
- Suitable for solvent and solventless silicone
- Colour: White
- Application: For silicone treatment on both sides (adhesive tapes)

Specifications

Target values at 23°C / 50% r.H. For general guidance only	Methods	Units							
Substance	ISO 536	g/m ²	90.0	92.0	95.0	100.0	120.0	130.0	140.0
Thickness	ISO 534	µm	76.0	78.0	80.0	85.0	100.0	108.0	116.0
Roughness PPS WS	ISO 8791-4	µm*100	200.0	200.0	200.0	210.0	210.0	220.0	220.0
Roughness PPS FS	ISO 8791-4	µm*100	190.0	190.0	190.0	200.0	200.0	210.0	210.0
Tensile strength MD	ISO 1924	N/15mm	133.0	137.0	140.0	145.0	170.0	179.0	190.0
Tensile strength CD	ISO 1924	N/15mm	75.0	76.0	77.0	81.0	92.0	97.0	103.0
Cobb Unger 120 sec. WS	Internal method	g/m ²	1.1	1.1	1.1	1.1	1.3	1.3	1.3
Cobb Unger 120 sec. FS	Internal method	g/m ²	0.9	0.9	0.9	0.9	1.1	1.1	1.1
Technical Specification		Nr.	111/007	109/010	883/002	751/004	544/005	736/004	752/004

Edition: June 10

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cartiera di Carmignano guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.