



Cham Paper Group

Technical Data Sheet

Name **Silco White PE BS**

Structure

glassine paper

Features

- Glassine paper for PE extrusion on both sides
- Highly calendered
- Colour: White
- Application: For PE extrusion on both sides and technical applications

Specifications

Target values at 23°C / 50% r.H. for general guidance only	Methods	Units	Provis orial	
Substance	ISO 536	g/m ²	60.0	88.0
Thickness	ISO 534	µm	54.0	78.0
Roughness PPS WS	ISO 8791-4	µm*100	220.0	220.0
Roughness PPS FS	ISO 8791-4	µm*100	220.0	220.0
Tensile strength MD	ISO 1924	N/15mm	80.0	120.0
Tensile strength CD	ISO 1924	N/15mm	40.0	65.0
Technical specification		Nr.	---/--	---/--

Edition: January 2011

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cham Paper Group Italia S.p.A. guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.