



Cham Paper Group

Technical Data Sheet

Name TRENNCAR 3

Structure



Features

- One side release coated kraft paper
- Very good and stable release properties
- High strength properties
- Good runnability
- Good heat resistance (neutral sized)
- 100% ink yield on transfer
- Suitable for rotogravure printing
- **Application:** base paper for casting of coucthouc or for other natural rubber

Specifications

Target values at 23°C / 50% r. H. for general guidance only	Methods	Units	
Substance	ISO 536	g/m ²	90.0
Brightness R457	DIN 53145	%	83.0
Opacity	ISO 2471	%	82.0
Roughness PPS H10 WS	ISO 8791-4	µm*100	300.0
Roughness PPS H10 FS	ISO 8791-4	µm*100	370.0
Tensile strength MD	ISO 1924	N/15mm	100.0
Tensile strength CD	ISO 1924	N/15mm	66.0
Release strength coated side	180° FINAT 1-24 h	gf/25mm	120.0
Humidity absolute	ISO 287	%	4.0

Edition: October 2013

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. Cartiera di Carmignano guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.